
	<b>Declaration of Performance</b>	<b>No.</b> R80/CPR/14351/17	 EN 14351-1	<b>Year of issue</b> 16
---	-----------------------------------	--------------------------------	---	----------------------------

1. Unique identification code of the product-type: **DXF DU8 (80CDxx), DXF DU6 (80CCxx), DMF DU6 (80CExx), DMF DU8 (80CFxx), DEF DU6 (80CGxx), DEF DU8 (80CHxx), DXF DU6 ColourLine (80EDxx), DMF DU6 ColourLine (80EExx), DEF DU6 ColourLine (80EFxx), DXF DU8 ColourLine, DMF DU8 ColourLine, DEF DU8 ColourLine (RB-xxxxxx)**
2. Intended use: **PVC flat roof windows intended for installation in residential and commercial buildings.**
3. Manufacturer: **FAKRO PP Sp. z o.o.  
ul. Węgierska 144a,  
33-300 Nowy Sącz, Poland  
fakro@fakro.pl**
4. Authorised representative: **./.**
5. System of assessment and verification of constancy of performance: **3**
6. Harmonised standard: **EN 14351-1:2006+A2:2016**  
Notified body: **Building Research Institute (notification No. 1488), performed initial type test in system 3 (included in points 7.1-7.11) and prepared classification report.**
7. Declared performance:

Essential characteristics	Performance		Harmonised technical specification
	DXF/DMF/DEF		
	DU6	DU8	
7.1 Resistance to wind load	Class C5/B5 (1) Class C2/B2 (2)		4.2
7.2 Resistance to snow load	6H-18-4H-18-44.2 (3) 6H-16-4H-18-55.2 (3)	6H-10-4H-10-4H-12-44.2 (3)	4.3
7.3 Reaction to fire	B-s2,d0		4.4
7.4 External fire performance	B <sub>ROOF</sub> (t1)		4.4
7.5 Watertightness. Non-shielded (A)	E1200		4.5
7.6 Impact resistance	Class 5 – 950mm		4.7
7.7 Load-bearing capacity of safety device	npd (4)		4.8
7.8 Acoustic performance [dB]	34 (-1,-4)	33 (-1,-3)	4.11
7.9 Thermal transmittance [W/m²K]	0.70 (5)	0.64 (5)	4.12
7.10 Radiation properties: - Solar factor g - Light transmittance	0.43 0.54	0.38 0.49	4.13
7.11 Air permeability	Class 4		4.14

(1) for the windows with the width of ≤140 cm and height of ≤140 cm, (2) for the windows with the width of >140 cm and height of >140 cm, (3) H – toughened glass, (4) npd – no performance determined, (5) reference dimension (1,23 x 1,48 m) – calculation according to standard PN-EN ISO 10077-1, p. 6.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:



Ewa Łukaszczyk-Haslik  
(Certification and Quality Control Director)

Nowy Sącz, 04/09/2017